ASSEMBLY OCCUPANCIES

OWNER / OCCUPANT INSPECTION INFORMATION



The B.C. Fire Code requires building owners/occupants to comply with the requirements on this checklist.

These requirements are in addition to those listed in the Fire Safety & You brochure.

ASSEMBLY USES INCLUDE:

Places used for gatherings of people, such as:

- places of worship
- nightclubs/pubs
- · community halls
- libraries
- restaurants



CITY OF SURREY FIRE SERVICE

8767 132 Street Surrey B.C., V3W 4P1

Fire Prevention: 604-543-6780 Email: fireprevention@surrey.ca Fax: 604-594-1237

www.surrey.ca

Checklist: Common Fire Service Requirements

Address: must be visible from road and lane, free from foliage, trees, etc. and in a contrasting colour.
Aisleways: must provide a clear access to exits.
Decorations: must be non-combustible or treated.
Drapes: must be treated.
Emergency lighting: may be provided by battery packs with remote and attached heads, or by emergency generators that will illuminate specified A/C fixtures or remote light heads. Must be operational, with no visible damage, and serviced and tagged annually by a certified technician.
Exit doors: must not be locked or blocked from either the inside or outside. Must be unlocked from the inside when the building is occupied. Must have panic hardware that releases when a force of 20 pounds or less is applied.
Exit signs: must be visible and remain illuminated at all times the building is occupied.
Extension cords: kept to a minimum and not overloaded.
Fire alarm systems: must have a working A/C power-on bulb and be in good working condition with no audible or visual damage. Must have a current service tag (within the last 12 months) and up-to-date logbook.
Fire doors : must not be blocked or wedged open, including stairwell doors. Must have closures and no wedges to hold open fire rated doors.
Fire Safety Plan: Must be reviewed and revised yearly.
Fire hydrants: must be accessible, free of damage and serviced within the specified date. Private hydrants require annual service, with records kept on site.
Fire separations: must have no holes or openings that compromise their purpose.
Garbage disposal: commercial containers must be located three metres from combustible buildings. If inside, commercial containers should have tight-fitting lids and be in fire-separated rooms.
Occupant load: Submit occupant load calculation per B.C. Fire Code requirements to Fire Prevention Branch Office for review.
Portable fire extinguishers: must: ☐ be located adjacent to corridors or aisles that provide access to exits. ☐ be mounted in a visible location, accessible, and serviced and tagged at least once

☐ be full and functioning (no damage, corrosion, leaks, malfunctioning parts or

☐ **Portable heaters:** must be an approved type and kept away from combustibles.

every 12 months by a certified technician.

clogged nozzles).

☐ have a minimum rating 2A-10BC.